

DIE STARKE ACCULUX EX SLE PRODUKTFAMILIE

Eigene, immer erreichbare
und qualifizierte AccuLux
Service-Abteilung.

Leuchtenkopf
110° schwenkbar

EX-Zone 1/21 und 2/22

Für alle Gase
und Stäube im
EX-Bereich
einsetzbar!



IP 64



einfache Bedienung

Ladezustandsanzeige



Mit Notlichtfunktion - geht an, wenn alle anderen Lichter ausgehen!

Auch ohne Notlichtfunktion (für Montage in Fahrzeugen) und ohne EX-Schutz (SL-Produktfamilie) erhältlich.

Als Glühlampen-, Power LED- oder Power LED Focus-Ausführung erhältlich!

Unabhängig vom Fraunhofer IZM getestet!



Made in Germany!



ACCULUX EX SLE 15, EX SLE 15 LED, EX SLE 16 LED

Ausführung	als Glühlampen-, Power LED- oder Power LED Focus-Ausführung erhältlich
Leuchtstärke	bis ca. 180 Lumen / 3 Leuchtmodi (Hauptlicht, Hauptlicht blinkend, Notlicht)
Leuchtdauer	bis ca. 5 / 75 Stunden
Leuchtweite	bis max. 170 m
Bedienung	einfache Bedienung mittels Druckschalter (auch mit Handschuhen)
Ladung	in Fahrzeugen (12/24 V DC) und Gebäuden (230 V AC)
Lieferumfang	Leuchte, Ladestation, KfZ-Ladekabel 12/24 V, Netzkabel 230 V, Vorsatzscheibe weiß und orange
Qualität	unabhängige Überprüfung durch das Fraunhofer Institut



Synonym für ladbares Licht – auch für die explosionsgeschützten Bereiche.

www.accumlux.de



THE STRONG ACCULUX EX SLE PRODUCT FAMILY

Always available
and qualified AccuLux
service department.

110° swivelling
lamp head

EX-zones 1/21 and 2/22

Can be used
for all gases
and dusts in
EX-areas!



IP 64



easy operating

charge level indicator



With emergency light function - comes on when all other lights go out!

Also available without emergency lighting function (for assembly in vehicles) and as non-EX-version (SL product family).

Available as a bulb, power LED or power LED focus version!

Independently tested by Fraunhofer IZM!




Made in Germany!



ACCULUX EX SLE 15, EX SLE 15 LED, EX SLE 16 LED

Version	available as a bulb, power LED or power LED focus version
Luminous flux	up to ca. 180 lm / 3 light modes ((main light, flashing main light, emergency light)
Operating time	up to ca. 5 / 75 h
Operating range	up to max. 170 m
Operation	easy operating by a pressure switch (also with gloves)
Charging	in vehicles (12/24 V DC) and buildings (230 V AC)
Supply	lamp, charging unit, vehicle DC plug 12/24V, AC cable 230V, diffusers white and orange
Quality	independently tested by Fraunhofer IZM



Synonym for chargeable light - also for explosion-protected areas.

www.accumlux.de

