


DIE STARKEN KLEINEN. EX-GESCHÜTZT. VON ACCULUX. WENN'S MAL ETWAS KLEINER (IN EX) SEIN MUSS

HL 10 EX

bis 5m Tiefe wasserdicht
Hell und stoßfest!



Signalkegel
(optional erhältlich)



auch als Helmleuchte
verwendbar (Helmhalterung
optional erhältlich)



STL 1 EX

einstellbarer Neigungswinkel
zwei Leuchtstufen
superhelle Power LED

MHL 5 EX

Klein, fein,
immer dabei!




Für alle Gase
und Stäube im
EX-Bereich
einsetzbar!



Made in Germany!

ACCULUX	HL 10 EX	MHL 5 EX	STL 1 EX
EX-Zonen	1, 2, 21, 22	1, 2, 21, 22	0, 1, 2
Schutzart	IP 68	IP 68	IP 67
Leuchtstärke	ca. 110 Lumen	ca. 60 Lumen	ca. 90 / 170 Lumen 2 Leuchtstufen
Leuchtdauer	ca. 11 Stunden	ca. 4 Stunden	ca. 13 / 6,5 Stunden
Leuchtweite	ca. 150 m	ca. 30 m	ca. 100 m
Batterien	4 x AA	2 x AAA	3 x AAA
Zubehör	Helmhalterung (Art. Nr. 492845) Signalkegel (Art. Nr. 492850)		



Synonym für Licht - auch für die explosionsgeschützten Bereiche.

www.acculux.de




THE STRONG LITTLE ONES. EX-PROOFED. FROM ACCULUX. IF IT HAS TO BE A LITTLE BIT SMALLER (IN EX).

HL 10 EX

up to 5m depth waterproof
bright and shock proofed!



signal cone
(optionally available)



can also be used as helmet
lamp (helmet holder optionally
available)



STL 1 EX

flexible head
2 step switch
extreme bright Power LED

MHL 5 EX

small and
handy!



Applicable for
all gases and
dusts in the
EX area!



Made in Germany!

ACCULUX	HL 10 EX	MHL 5 EX	STL 1 EX
EX-zones	1, 2, 21, 22	1, 2, 21, 22	0, 1, 2
Protection type	IP 68	IP 68	IP 67
Luminous flux	ca. 110 lm	ca. 60 lm	ca. 90 / 170 lm 2 light modes
Operating time	ca. 11 h	ca. 4 h	ca. 13 / 6,5 h
Operating range	ca. 150 m	ca. 30 m	ca. 100 m
Batteries	4 x AA	2 x AAA	3 x AAA
Accessories	helmet holder (Art. Nr. 492845) signal cone (Art. Nr. 492850)		



Synonym for light - also for explosion-protected areas.

www.acculux.de

